

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 June 2006 (22.06.2006)

PCT

(10) International Publication Number
WO 2006/064220 A1

(51) International Patent Classification:
B01D 33/03 (2006.01) **B07B 1/46** (2006.01)

(21) International Application Number:
PCT/GB2005/004814

(22) International Filing Date:
14 December 2005 (14.12.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0427756.2 18 December 2004 (18.12.2004) GB

(71) Applicant (for all designated States except US): **UNITED WIRE LIMITED** [GB/GB]; Granton Park Avenue, Granton, Edinburgh EH5 1HT (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **ROBERTSON, Graham, Alexander** [GB/GB]; 52 Rannoch Road, Edinburgh EH4 7EN (GB).

(74) Agent: **KEITH W NASH & CO**; 90-92 Regent Street, Cambridge CB2 1DP (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: IMPROVEMENTS IN AND RELATING TO SIFTING SCREENS



(57) Abstract: A frame over which woven wire mesh is to be stretched and secured to form a sieving screen and which can be used to screen solids from drilling mud recovered from downhole when drilling for oil or gas. The frame comprises a rectilinear moulded plastic frame having edge regions by which it is secured in place in a shaker. Within the frame is a plurality of rectilinear windows formed by an orthogonal array of intersecting ribs also of moulded plastics material. Some of the ribs are internally reinforced by a structure comprising two spaced apart layers of orthogonal intersecting spaced apart wires, running parallel to the length and breadth of the rectilinear shape of the frame within the ribs to increase their rigidity. The edge regions of the frame are reinforced internally by metal box-section members joined at their four corners and defining perimeter reinforcement, and the ends of the wires are secured to the box-section members. The latter are encapsulated in the same plastics material from which the orthogonal array of intersecting ribs are moulded. Alternate ribs are not reinforced with wires, and the non-reinforced ribs only extend partway between the upper and lower faces of the frame. Lengths of wire bent to form spacers and adapted to fit between upper and lower wires of the rib reinforcing structure, are joined to the upper and lower wires so as to extend therebetween and maintain the desired separation of the two layers of wires during the plastics encapsulation/moulding process.

WO 2006/064220 A1